



FIRE EXTINGUISHER SPECIFICATIONS

PART #	WATER CAPACITY			DIAMETER		LENGTH		CYLINDER WEIGHT		CO ₂	
	cu in	lbs	liters	in	mm	in	mm	lbs	kgs	lbs	kgs
F5	203.4	7.4	3.33	5.25	133.4	14.2	361	6.3	2.9	5.0	2.27
F10	407.1	14.7	6.67	6.89	175.0	16.5	419	12.3	5.6	10.0	4.50
F15	611.7	22.1	10.00	6.89	175.0	23.1	587	16.2	7.3	15.0	6.80
F17	665.0	24.0	10.80	8.60	218.4	17.9	454	25.0	11.3	16.3	7.40
F20	813.8	29.4	13.30	8.00	203.2	23.2	589	23.1	10.5	20.0	9.07

Service Pressure: - 1800 psi / 124 bar

Specification: - DOT-3AL & TC-3ALM designed
 - ISO design cylinders are available
 - UL Approval on F5, F10, F15 and F20 cylinders

Alloy: - Manufactured from high strength aluminum alloy 6061-T6

Threads: - F5, F10, F15 & F20 supplied with 1.125-12UNF-2B
 - F17 supplied with 1.625-12-UNF-3B
 - Other thread sizes available upon request

Markings: - As required by specification
 - Additional markings available upon request

Finish: - Standard finish is red paint

Graphics: - Logos or labels in silkscreen or Duragrafix available upon request

sales@catalinacylinders.com
www.catalinacylinders.com

Catalina Cylinders - West

7300 Anaconda Avenue, Garden Grove, CA 92841
 tel 714-890-0999 fax 714-890-1744

Catalina Cylinders - East

2400 Aluminum Avenue, Hampton, VA 23661
 tel 757-896-9100 fax 757-896-0206