



## SCUBA SPECIFICATIONS

PART #	WATER				CYLINDER				BUOYANCY			
	Capacity cu ft*	cu in	CAPACITY		DIAMETER		LENGTH		WEIGHT		LBS	
		lbs	liters	in	mm	in	mm	lbs	kgs	full	500 psi	empty

### 3300 SERIES - 3300 PSI (228 BAR)

<b>C100</b>	807	29.2	13.2	8.00	203.2	26.5	673	42.0	19.1	-5.2	0.6	2.2
<b>C80</b>	625	22.6	10.3	7.25	184.2	25.5	648	34.7	15.7	-5.8	-1.3	0.0
<b>C60</b>	486	17.5	7.9	7.25	184.2	19.9	506	27.3	12.4	-5.6	-2.1	-1.2

### 3000 SERIES - 3000 PSI (207 BAR)

<b>S80</b>	678	24.5	11.1	7.25	184.2	25.9	658	31.3	14.2	-1.6	2.8	4.1
<b>S63</b>	552	19.9	9.0	7.25	184.2	21.7	551	26.9	12.2	-2.8	0.7	1.8
<b>S53</b>	464	16.8	7.6	7.25	184.2	19.2	488	25.1	11.4	-3.8	-0.8	0.1
<b>S50</b>	438	15.9	7.2	6.89	175.0	19.4	493	21.8	9.9	-2.4	0.4	1.2
<b>S45</b>	394	14.2	6.4	6.89	175.0	17.7	450	20.3	9.2	-2.8	-0.3	0.5
<b>S40</b>	350	12.7	5.8	5.25	133.4	25.4	645	16.2	7.3	-1.5	0.7	1.4
<b>S30</b>	263	9.5	4.3	5.25	133.4	19.9	505	13.6	6.2	-2.4	-0.7	-0.2
<b>S19</b>	166	6	2.7	4.38	111.3	17.7	450	7.8	3.5	-1.5	-0.4	-0.2
<b>S13</b>	114	4.1	1.9	4.38	111.3	12.8	325	5.7	2.6	-1.8	-1.0	-0.9
<b>S6</b>	53	1.9	0.9	3.21	81.5	10.8	274	2.6	1.2	-1.5	-1.2	-1.2
<b>S4</b>	35	1.3	0.6	3.21	81.5	7.8	198	1.9	0.9	-1.6	-1.4	-1.4

\* All capacities are exact except the industry standard S80 & C80 which have an actual capacity of 77.4 cu ft

- Specification:** - DOT-3AL & TC-3ALM design; ISO design cylinders are available  
**Alloy:** - Manufactured from high strength aluminum alloy 6061-T6  
**Threads:** - Standard 3/4-14 NPSM; Other thread sizes available upon request  
**Markings:** - As required by specification; Additional markings available upon request  
**Finish:** - Shot blasted, fully brushed & powder coat finishes available  
**Graphics:** - Logos or labels in silkscreen or Duragrafix available upon request  
**Accessories:** - Valves installed upon request

## SCBA SPECIFICATIONS

PART #	WATER		SERVICE		CYLINDER				AIR			
	CAPACITY		PRESSURE		DIAMETER		LENGTH		WEIGHT		CAPACITY	
	lbs	liters	psi	bar	in	mm	in	mm	lbs	kgs	cu ft	liters
<b>9044</b>	3.3	1.5	2216	153	4.38	111	10.0	255	3.8	1.7	7.9	224
<b>9046</b>	4.8	2.2	3000	207	4.38	111	14.6	370	6.9	3.1	15.2	430
<b>9076</b>	18.6	8.5	2216	153	6.75	171	21.4	544	18.5	8.4	45.0	1275

**Threads:** - Standard 3/4-16 UNF; Other thread sizes available upon request

[sales@catalinacylinders.com](mailto:sales@catalinacylinders.com)  
[www.catalinacylinders.com](http://www.catalinacylinders.com)

### Catalina Cylinders West

7300 Anaconda Avenue, Garden Grove, CA 92841  
 tel 714-890-0999 fax 714-890-1744

### Catalina Cylinders East

2400 Aluminum Avenue, Hampton, VA 23661  
 tel 757-896-9100 fax 757-896-0206