



## ISO APPROVED & CE MARKED SCUBA SPECIFICATIONS

| PART #                                  | WATER              |       |      |        | CYLINDER |      |        |      | BUOYANCY |      |      |         |       |
|---|--------------------|-------|------|--------|----------|------|--------|------|----------|------|------|---------|-------|
|   | Capacity<br>cu ft* | cu in | lbs  | liters | DIAMETER |      | LENGTH |      | WEIGHT   |      | full | LBS     |       |
|   |                    |       |      |        | in       | mm   | in     | mm   | lbs      | kgs  |      | 500 psi | empty |
| <b>3000 SERIES - 3000 PSI (207 BAR)</b> |                    |       |      |        |          |      |        |      |          |      |      |         |       |
| <b>CE S80</b>                           | 678                | 24.5  | 11.1 | 7.25   | 184.2    | 25.9 | 658    | 31.3 | 14.2     | -1.6 | 2.8  | 4.1     |       |
| <b>CE S63</b>                           | 552                | 19.9  | 9.0  | 7.25   | 184.2    | 21.7 | 551    | 26.9 | 12.2     | -2.8 | 0.7  | 1.8     |       |
| <b>CE S53</b>                           | 464                | 16.8  | 7.6  | 7.25   | 184.2    | 19.2 | 488    | 25.1 | 11.4     | -3.8 | -0.8 | 0.1     |       |
| <b>CE S40</b>                           | 350                | 12.7  | 5.8  | 5.25   | 133.4    | 25.4 | 645    | 16.2 | 7.3      | -1.5 | 0.7  | 1.4     |       |
| <b>CE S30</b>                           | 263                | 9.5   | 4.3  | 5.25   | 133.4    | 19.9 | 505    | 13.6 | 6.2      | -2.4 | -0.7 | -0.2    |       |
| <b>CE S14</b>                           | 124                | 4.5   | 2.0  | 5.25   | 133.4    | 10.4 | 263    | 7.2  | 3.3      |      |      |         |       |

\* All capacities are exact except the industry standard S80 which has an actual capacity of 77.4 cu ft

- Specification:** - ISO 7866 designed  
- DOT-3AL & TC-3ALM available
- Alloy:** - Manufactured from high strength aluminum alloy 6061-T6
- Threads:** - M25  
- Other thread sizes available upon request
- Markings:** - As required by specification  
- Additional markings available upon request
- Finish:** - Shot blasted, fully brushed & powder coat finishes available
- Graphics:** - Logos or labels in silkscreen or Duragrafix available upon request
- Accessories:** - Valves installed upon request

[sales@catalinacylinders.com](mailto:sales@catalinacylinders.com)  
[www.catalinacylinders.com](http://www.catalinacylinders.com)

**Catalina Cylinders West**  
7300 Anaconda Avenue, Garden Grove, CA 92841  
tel 714-890-0999 fax 714-890-1744

**Catalina Cylinders East**  
2400 Aluminum Avenue, Hampton, VA 23661  
tel 757-896-9100 fax 757-896-0206