



## FIRE EXTINGUISHER SPECIFICATIONS

PART #	WATER			CYLINDER									
	CAPACITY			DIAMETER		LENGTH		WEIGHT		CO <sub>2</sub>		NITROGEN	
	cu in	lbs	liters	in	mm	in	mm	lbs	kgs	lbs	kgs	cu ft	liters
<b>F5</b>	203.4	7.4	3.33	5.25	133.4	14.2	361	6.3	2.9	5.0	2.27	14.5	410.6
<b>F10</b>	407.1	14.7	6.67	6.89	175.0	16.5	419	12.3	5.6	10.0	4.50	29.0	821.3
<b>F15</b>	611.7	22.1	10.00	6.89	175.0	23.1	587	16.2	7.3	15.0	6.80	43.3	1226.0
<b>F17</b>	665.0	24.0	10.80	8.60	218.4	17.9	454	25.0	11.3	16.3	7.40	47.0	1330.0
<b>F20</b>	813.8	29.4	13.30	8.00	203.2	23.2	589	23.1	10.5	20.0	9.07	576.0	1631.0

**Service Pressure:** - 1800 psi / 124 bar

**Specification:** - DOT-3AL & TC-3ALM designed  
 - ISO design cylinders are available

**Alloy:** - Manufactured from high strength aluminum alloy 6061-T6

**Threads:** - F5, F10, F15 & F20 supplied with 1.125-12UNF-2B  
 - F17 supplied with 1.625-12-UNF-3B  
 - Other thread sizes available upon request

**Markings:** - As required by specification, inclusive of tare weight  
 - Additional markings available upon request

**Finish:** - Standard finish is brushed body with unpainted crown

**Graphics:** - Logos or labels in silkscreen or Duragrafix available upon request

**Common Configuration:** - F10 and larger with valve & carrying handle, F5 with valve only  
 - Caps & collars or dip tubes available upon request

[sales@catalinacylinders.com](mailto:sales@catalinacylinders.com)  
[www.catalinacylinders.com](http://www.catalinacylinders.com)

**Catalina Cylinders West**

7300 Anaconda Avenue, Garden Grove, CA 92841  
 tel 714-890-0999 fax 714-890-1744

**Catalina Cylinders East**

2400 Aluminum Avenue, Hampton, VA 23661  
 tel 757-896-9100 fax 757-896-0206