



World Class Products. First Class Service



9000 SERIES SPECIFICATIONS

PART NO.	SERVICE				CO2		AIR	WATER	O-RING SEAT	
	PRESSURE (psi / bar)	DIAMETER (in / mm)	LENGTH (in / mm)	WEIGHT (lbs / kgs)	CAPACITY (lbs / kgs)	CAPACITY (cu ft / L)	VOLUME (cu in / L)	DIAMETER (in / mm)	THREADS	
9003	1800 / 124	2.00 / 51	5.38 / 137	.47 / .21	.23 / .10	.7 / 19	9 / .15	.750 / 19.1	5/8-18 UNF	
9001	1800 / 124	2.00 / 51	9.45 / 240	.79 / .35	.45 / .20	1.3 / 37	18 / .30	.750 / 19.1	5/8-18 UNF	
9002	1800 / 124	2.00 / 51	13.09 / 333	1.1 / .49	.66 / .30	1.9 / 54	27 / .44	.750 / 19.1	5/8-18 UNF	
9057	1800 / 124	2.50 / 63	9.35 / 237	1.0 / .45	.75 / .34	2.2 / 63	31 / .51	.750 / 19.1	5/8-18 UNF	
9182	1800 / 124	2.75 / 70	10.00 / 254	1.2 / .54	1.00 / .45	2.9 / 83	41 / .67	.769 / 19.5	3/4-16 UNF	
9048	1800 / 124	3.20 / 81	7.83 / 199	1.3 / .59	1.00 / .45	2.9 / 83	41 / .67	1.018 / 25.9	3/4-16 UNF	
9055	1800 / 124	3.20 / 81	9.38 / 238	1.5 / .68	1.25 / .57	3.7 / 103	51 / .84	.750 / 19.1	5/8-18 UNF	
9042	1800 / 124	3.20 / 81	11.08 / 281	1.7 / .78	1.50 / .68	4.4 / 124	61 / 1.00	1.018 / 25.9	3/4-16 UNF	
9090	1800 / 124	3.20 / 81	12.48 / 317	1.9 / .88	1.75 / .79	5.1 / 145	71 / 1.16	1.018 / 25.9	3/4-16 UNF	
9147	2216 / 153	2.36 / 60	11.81 / 300	1.3 / .60	.88 / .40	7.4 / 209	32 / .53	.922 / 23.4	M18 X 1.5	
9044	2216 / 153	4.38 / 111	10.03 / 255	3.8 / 1.74	2.48 / 1.13	7.9 / 224	91 / 1.5	1.018 / 25.9	3/4-16 UNF	
9010	3000 / 207	2.00 / 51	7.33 / 186	.68 / .31	.32 / .14	1.5 / 42	13 / .21	.750 / 19.1	5/8-18 UNF	
9167	3000 / 207	2.00 / 51	9.25 / 235	.84 / .38	.43 / .19	2.0 / 57	18 / .30	.750 / 19.1	5/8-18 UNF	
9009	3000 / 207	2.00 / 51	11.38 / 289	1.0 / .46	.54 / .24	2.5 / 71	22 / .36	.750 / 19.1	5/8-18 UNF	
9179	3000 / 207	2.36 / 60	11.68 / 297	1.5 / .66	.82 / .38	5.3 / 151	31 / .50	.922 / 23.4	M18 X 1.5	
9098	3000 / 207	3.20 / 81	11.17 / 283	2.7 / 1.22	1.44 / .65	6.0 / 171	53 / .87	.750 / 19.1	5/8-18 UNF	
9046	3000 / 207	4.38 / 111	14.58 / 370	6.5 / 2.96	3.62 / 1.64	15.2 / 431	133 / 2.19	1.018 / 25.9	3/4-16 UNF	

Service Pressure: - 1800, 2216, and 3000 psi

Specification: - DOT-3AL & TC-3ALM designed
- ISO design cylinders are available

Alloy: - Manufactured from high strength aluminum alloy 6061-T6

Threads: - Cylinders supplied with 5/8-18UNF, 3/4-16 UNF and M18 X 1.5
- Other thread sizes available upon request

Markings: - As required by specification
- Additional markings available upon request

Finish: - Brushed exterior

Graphics: - Logos or labels in silkscreen or Duragrafix available upon request

jwolff@catalinacylinders.com

www.catalinacylinders.com

Catalina Cylinders - East

2400 Aluminum Avenue, Hampton, VA 23661

tel 757-896-9100 fax 757-896-0206