



World Class Products. First Class Service



PORTABLE CALIBRATION GAS CYLINDER SPECIFICATIONS

PART NO.	GAS CAPACITY (Liters)	SERVICE PRESSURE (Bar)	DIAMETER (mm)	LENGTH (mm)	WATER VOLUME (Liters)	THREADS	DESIGN SPECIFICATION	ALLOY
2724	17	34	64	172	0.42	1"-14UNF	DOT 39 / TC 39M	3003
2705	34	34	74	271	0.92	1"-14UNF	DOT 39 / TC 39M	3003
2611	58	34	89	346	1.72	1"-14UNF	DOT 39 / TC 39M	3003
2689 ₍₁₎	58	34	89	346	1.72	1"-14UNF	ISO 11118	3003
2545	76	34	102	350	2.22	1"-14UNF	DOT 39 / TC 39M	3003
1602	96	34	102	436	2.85	1"-14UNF	DOT 39 / TC 39M	3003
9260 ₍₁₎	116	69	89	355	1.60	1"-14UNF	ISO 11118	6061
9217	108	83	81	326	1.29	1"-14UNF	DOT 3AL / TC-3ALM	6061
9299	75	90	74	268	0.84	1"-14UNF	ISO 7866	6061
9276	150	90	89	355	1.60	1"-14UNF	ISO 7866	6061

Capacities and dimensions above are nominal designations.

Specification: - DOT 39 & TC-39M

- ISO 7866 Refillable

- ISO 11118 Non Refillable

(1) Non Refillable valve required

Alloy: - Reference alloys designated above

Threads: - Cylinders supplied with 1.0"-14UNF-2B threads

- Other thread sizes available upon request

Markings: - As required by specification

- Additional markings available upon request

Finish: - Natural exterior

- Other finishes available upon request

Graphics: - Logos or labels in silkscreen or Duragrafix available upon request

jwolff@catalinacylinders.com

www.catalinacylinders.com

Catalina Cylinders - East

2400 Aluminum Avenue, Hampton, VA 23661

tel 757-896-9100 fax 757-896-0206