



ISO APPROVED & CE MARKED SCUBA SPECIFICATIONS

PART #	WATER CAPACITY			DIAMETER		LENGTH		CYLINDER WEIGHT		BUOYANCY LBS		
	Capacity cu ft*	cu in	lbs	liters	in	mm	in	mm	lbs	kgs	full	500 psi

3000 SERIES - 3000 PSI (207 BAR)

CE S80	678	24.5	11.1	7.25	184.2	25.9	658	31.3	14.2	-1.6	2.8	4.1
CE S63	552	19.9	9.0	7.25	184.2	21.7	551	26.9	12.2	-2.8	0.7	1.8
CE S53	464	16.8	7.6	7.25	184.2	19.2	488	25.1	11.4	-3.8	-0.8	0.1
CE S40	350	12.7	5.8	5.25	133.4	25.4	645	16.2	7.3	-1.5	0.7	1.4
CE S30	263	9.5	4.3	5.25	133.4	19.9	505	13.6	6.2	-2.4	-0.7	-0.2

* All capacities are exact except the industry standard S80 which has an actual capacity of 77.4 cu ft

- Specification:**
- ISO 7866 designed
 - DOT-3AL & TC-3ALM available
- Alloy:**
- Manufactured from high strength aluminum alloy 6061-T6
- Threads:**
- M25
 - Other thread sizes available upon request
- Markings:**
- As required by specification
 - Additional markings available upon request
- Finish:**
- Shot blasted, fully brushed & powder coat finishes available
- Graphics:**
- Logos or labels in silkscreen or Duragrafix available upon request
- Accessories:**
- Valves installed upon request

sales@catalinacylinders.com
www.catalinacylinders.com

Catalina Cylinders Inc.
 7300 Anaconda Avenue, Garden Grove, CA 92841
 tel 714-890-0999 fax 714-890-1744

Catalina Cylinders Inc. / Cliff Impact
 2400 Aluminum Avenue, Hampton, VA 23661
 tel 757-896-9100 fax 757-896-0206